Record Nr. Titolo	UNINA9910135768103321 ANSI/IEEE Std C57.92-1981 : IEEE Guide for Loading Mineral-Oil- Immersed Power Transformers up to and Including 100 Mva With 55 Degrees C Or 65 Degrees C Average Winding Rise / / Institute of Electrical and Electronics Engineers
Pubbl/distr/stampa	New York, New York : , : IEEE, , 1981
ISBN	0-7381-4302-2
Descrizione fisica	1 online resource
Disciplina	621.314
Soggetti	Electric apparatus and appliances - Protection Electric transformers
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Sommario/riassunto	This guide covers general recommendations for loading mineral-oil- immersed power transformers, manufactured in accordance with ANSI C57.12.10-1976 and ANSI C57.12.30-1977 and other oil-insulated power transformers up to and including 100 MVA maximum nameplate rating. It is based mostly on aging of the winding insulation. Loading of transformers larger than 100 MVA may be limited by factors other than insulation aging such as stray flux, etc. When it is known that such limitations do not exist and insulation aging rather than oil temperature, gassing, tank heating, etc., is the controlling factor, this guide may be used. This guide may also be used for askarel filled transformers.

1.