

1. Record Nr.	UNINA9910142062203321
Titolo	Information technology . Part 3 Carrier sense multiple access with collision detection CSMA/CD access method and physical layer specifications : telecommunications and information exchange between systems--local and metropolitan area networks--specific requirements // Institute of Electrical and Electronics Engineers
Pubbl/distr/stampa	New York, New York : , : IEEE, , 2000
ISBN	0-7381-2473-7
Descrizione fisica	1 online resource (xxxvii, 1515 pages) : illustrations
Collana	IEEE Std ; ; Volume 802
Disciplina	004.62
Soggetti	Computer network protocols - Standards Data transmission systems - Standards Local Area Networks (Computer networks) - Standards
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Note generali	"IEEE Std 802.3ad-2000".
Nota di bibliografia	Includes bibliographical references.
Nota di contenuto	Figures -- References -- Citations -- Keywords -- Definitions -- Metrics -- Versions -- Footnotes.
Sommario/riassunto	Incorporating IEEE Std 802.3, 1998 Edition, IEEE Std 802.3ac-1998, IEEE Std 802.3ab-1999, and IEEE Std 802.3ad-2000. Superseded by 802.3-2002 (802.3ag). The media access control characteristics for the Carrier Sense Multiple Access with Collision Detection (CSMA/CD) access method for shared medium local area networks are described. The control characteristics for full duplex dedicated channel use are also described. Specifications are provided for MAU types 1BASE5 at 1 Mb/s; Attachment Unit Interface (AUI) and MAU types 10BASE5, 10BASE2, FOIRL (fiber optic inter-repeater link), 10BROAD36, 10BASE-T, 10BASE-FL, 10BASE-FB, and 10BASE-FP at 10 Mb/s; Media Independent Interface (MII) and PHY types 100BASE-T4, 100BASE-TX, 100BASE-FX, and 100BASE-T2 at 100 Mb/s; and the Gigabit MII (GMII) and 1000BASE-X PHY types, 1000BASE-SX, 1000BASE-LX, and 1000BASE-CX, which operate at 1000 Mb/s (Gigabit Ethernet) as well as PHY type 1000BASE-T. Repeater specifications are provided at each speed. Full duplex specifications are provided at the Physical Layer for 10BASE-T, 10BASE-FL, 100BASE-TX, 100BASE-FX, 100BASE-T2, and Gigabit

Ethernet. System considerations for multi-segment networks at each speed and management information base (MIB) specifications and additions to support Virtual Bridged Local Area Networks (VLANs) as specified in IEEE P802.1Q are also provided. Also specified is an optional Link Aggregation sublayer which multiple physical links to be aggregated together to form a single logical link.
