

1. Record Nr.	UNINA9910427686103321
Autore	Cabrera Mario
Titolo	Development of 15 micron cutoff wavelength HgCdTe detector arrays for astronomy // Mario Cabrera
Pubbl/distr/stampa	Cham, Switzerland : , : Springer, , [2020] ©2020
ISBN	3-030-54241-6
Edizione	[1st ed. 2020.]
Descrizione fisica	1 online resource (XVII, 121 p. 71 illus., 44 illus. in color.)
Collana	Springer Theses, Recognizing Outstanding Ph.D. Research, , 2190-5053
Disciplina	621.362
Soggetti	Infrared array detectors Mensuration & systems of measurement Materials science
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Nota di bibliografia	Includes bibliographical references.
Nota di contenuto	Chapter1: Introduction -- Chapter2: Test and Data Acquisition Setup -- Chapter3: Dark Current Theory -- Chapter4: Array Characterization -- Chapter5: Phase I Results: 13 m Cuto Wavelength Devices -- Chapter6: Phase II Results: 15 m Cuto Wavelength Devices -- Chapter7: Conclusions and Future Work.
Sommario/riassunto	This thesis describes advances in the understanding of HgCdTe detectors. While long wave (15 m) infrared detectors HgCdTe detectors have been developed for military use under high background irradiance, these arrays had not previously been developed for astronomical use where the background irradiance is a billion times smaller. The main pitfall in developing such arrays for astronomy is the pixel dark current which plagues long wave HgCdTe. The author details work on the success of shorter wavelength development at Teledyne Imaging Sensors, carefully modeling the dark current–reverse bias voltage curves of their 10 m devices at a temperature of 30K, as well as the dark current–temperature curves at several reverse biases, including 250 mV. By projecting first to 13 and then 15 m HgCdTe growth, values of fundamental properties of the material that would minimize tunneling dark currents were determined through careful modeling of the dark current–reverse bias voltage curves, as well as the

dark current-temperature curves. This analysis was borne out in the 13 m parts produced by Teledyne, and then further honed to produce the necessary parameters for the 15 m growth. The resulting 13 m arrays are being considered by a number of ground-based astronomy research groups.
