

1. Record Nr.	UNINA9910554813203321
Autore	Dinavahi Venkata
Titolo	Real-time electromagnetic transient simulation of AC-DC networks // Venkata Dinavahi, Ning Lin
Pubbl/distr/stampa	Hoboken, New Jersey : , : Wiley : , : IEEE Press, , [2021] ©2021
ISBN	1-119-69547-3 1-119-81903-2 1-119-69549-X
Descrizione fisica	1 online resource (595 pages)
Collana	IEEE Press series on power and energy systems
Disciplina	621.31921
Soggetti	Transients (Electricity) - Simulation methods Electronic books.
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Nota di bibliografia	Includes bibliographical references and index.
Nota di contenuto	Cover -- Title Page -- Copyright -- Contents -- About the Authors -- Preface -- Acknowledgments -- List of Acronyms -- Chapter 1 Field Programmable Gate Arrays -- 1.1 Overview -- 1.1.1 FPGA Hardware Architecture -- 1.1.2 Configurable Logic Block -- 1.1.3 Block RAM -- 1.1.4 Digital Signal Processing Slice -- 1.2 Multiprocessing Systemon Chip Architecture -- 1.3 Communication -- 1.4 HIL Emulation -- 1.4.1 Vivado® HighLevel Synthesis Tool -- 1.4.2 Vivado® TopLevel Design -- 1.4.3 Number Representation and Operations -- 1.4.4 FPGA Design Schemes -- 1.4.4.1 Pipeline Design Architecture -- 1.4.4.2 Parallel Design Architecture -- 1.4.5 FPGA Experiment -- 1.5 Summary -- Chapter 2 Hardware Emulation Building Blocks for Power System Components -- 2.1 Overview -- 2.2 Concept of HEBB -- 2.3 Numerical Integration -- 2.4 Linear Lumped Passive Elements -- 2.4.1 Model Formulation -- 2.4.1.1 Resistance R -- 2.4.1.2 Inductance L -- 2.4.1.3 Capacitance C -- 2.4.1.4 RL Branch -- 2.4.1.5 LC Branch -- 2.4.1.6 RLCG Branch -- 2.4.2 Hardware Emulation of Linear Lumped Passive Elements -- 2.5 Sources -- 2.5.1 Hardware Emulation of Sources -- 2.6 Switches -- 2.6.1 Hardware Emulation of Switches -- 2.7 Transmission Lines -- 2.7.1 Traveling Waves -- 2.7.2 Traveling Wave Model --

2.7.2.1 Modal Transformation -- 2.7.3 Hardware Emulation of the TWM
-- 2.7.3.1 Transformation Unit -- 2.7.3.2 Update Unit -- 2.7.4
Frequency Dependent Line Model -- 2.7.5 Hardware Emulation of FDLM
-- 2.7.5.1 Convolution Unit -- 2.7.5.2 Update Unit -- 2.7.6 Universal
Line Model -- 2.7.6.1 FrequencyDomain Formulation -- 2.7.6.2 Time
Domain Formulation -- 2.7.7 Hardware Emulation of the ULM --
2.7.7.1 Update x Unit -- 2.7.7.2 Convolution Unit -- 2.7.7.3
Interpolation Unit -- 2.8 Network Solver -- 2.8.1 Hardware Emulation
of Network Solver -- 2.8.2 Paralleled EMT Solution Algorithm.
2.8.3 MainControl Module -- 2.8.4 RealTime Emulation Case Study --
2.9 Nonlinear Elements: Iterative RealTime EMT Solver -- 2.9.1
Compensation Method -- 2.9.2 Newton-Raphson Method -- 2.9.3
Hardware Emulation of Nonlinear Solver -- 2.9.3.1 Nonlinear Function
Evaluation -- 2.9.3.2 Parallel Calculation of J and F(ikm) -- 2.9.3.3
Parallel Gauss-Jordan Elimination -- 2.9.3.4 Computing vc -- 2.9.4
Case Studies -- 2.10 Summary -- Chapter 3 Power Transformers -- 3.1
Overview -- 3.2 Nonlinear AdmittanceBased RealTime Transformer
Model -- 3.2.1 Linear Model Formulation -- 3.2.2 Linear Module
Hardware Design -- 3.2.3 Inode Unit Module -- 3.2.4 Nonlinear Model
Solution -- 3.2.4.1 Preisach Hysteresis Model -- 3.2.4.2 Nonlinear
Module Hardware Design -- 3.2.5 FrequencyDependent Eddy Current
Model -- 3.2.6 Hardware Emulation of Power Transformer -- 3.2.7
RealTime Emulation Case Studies -- 3.2.7.1 Case I -- 3.2.7.2 Case II
-- 3.3 Nonlinear Magnetic Equivalent Circuit Based Realtime Multi
Winding Transformer Model -- 3.3.1 Topological ST EMT Model --
3.3.1.1 ST Operating Principle -- 3.3.1.2 Tapselection Algorithm --
3.3.1.3 HighFidelity Nonlinear MECBased ST Model -- 3.3.1.4 Iron
Core Hysteresis and Eddy Currents -- 3.3.2 HighFidelity Nonlinear
MECBased ST Hardware Emulation -- 3.3.2.1 Network Transient
Emulation with Embedded ST -- 3.3.3 RealTime Emulation Case
Studies -- 3.3.3.1 Finite Element Modeling and Validation -- 3.3.3.2
Case Studies -- 3.4 RealTime FiniteElement Model of Power
Transformer -- 3.4.1 Magnetodynamic Problem Formulation -- 3.4.1.1
Refined TLM Solution -- 3.4.1.2 FieldCircuit Coupling -- 3.4.2
Hardware Emulation of Finite Element Model -- 3.4.3 Case Studies --
3.4.3.1 Results and Validation -- 3.4.3.2 Speedup and Scalability --
3.5 Summary -- Chapter 4 Rotating Machines -- 4.1 Overview -- 4.2
Lumped Universal Machine (UM) Model.
4.2.1 UM Model Formulation -- 4.2.2 Interfacing UM Model with
Network -- 4.2.3 UM HEBB -- 4.2.3.1 Speed & Angle Unit --
4.2.3.2 FrmTran Unit -- 4.2.3.3 Compidq0 Unit -- 4.2.3.4 Flux &
-- Torque Unit -- 4.2.3.5 Update & CompVc Unit -- 4.2.4 Real
Time Emulation Case Study -- 4.2.5 Overall Power System HEBB for
RealTime EMT Emulation -- 4.3 General Framework for StateSpace
Electrical Machine Emulation -- 4.3.1 FPGA Design Approaches for
Electrical Machine Emulation -- 4.3.2 StateSpace Representation of
Machine Models -- 4.3.3 System Configuration on FPGA -- 4.3.3.1
Number Representation -- 4.3.3.2 FloatingPoint Implementation by
VHDL -- 4.3.3.3 FixedPoint Implementation by Schematic -- 4.3.4
Evaluation of Designed Architectures -- 4.3.4.1 RealTime Emulation
Accuracy Assessment -- 4.3.4.2 Offline Validation -- 4.3.4.3 Hardware
Resource Utilization -- 4.3.5 RealTime Emulation Case Studies --
4.3.5.1 Case I: Induction Motor Transients -- 4.3.5.2 Case II:
Synchronous Generator Transients -- 4.3.5.3 Case III: Line Start
Permanent Magnet Synchronous Motor Transients -- 4.3.5.4 Case IV:
DC Motor Transients -- 4.4 Nonlinear Magnetic Equivalent Circuit
Based Induction Machine Model -- 4.4.1 Magnetic Circuit -- 4.4.2
Interfacing of Magnetic and Electric Circuits -- 4.4.3 Electric Circuit --

4.4.4 Nonlinear Solution of Detailed MEC -- 4.4.5 Hardware Emulation of Nonlinear MEC -- 4.4.5.1 Parallel Gauss-Jordan Elimination Unit -- 4.4.5.2 Parallel Computational Unit for Residual Vector -- 4.4.5.3 Nonlinear Evaluation Unit -- 4.4.6 Evaluation of RealTime Emulation of Induction Machine -- 4.5 Summary -- Chapter 5 Protective Relays -- 5.1 Overview -- 5.2 Hardware Emulation of Multifunction Protection System -- 5.2.1 Signal Processing HEBB -- 5.2.1.1 CORDIC HEBB -- 5.2.1.2 Symmetrical Components HEBB -- 5.2.1.3 DFT HEBB. 5.2.1.4 ZeroCrossing Detection HEBB -- 5.2.2 Multifunction Protective System HEBB -- 5.2.2.1 Fault Detection HEBB -- 5.2.2.2 Directional Overcurrent Protection HEBB -- 5.2.2.3 Over/Under Voltage Protection HEBB -- 5.2.2.4 Distance Protection HEBB -- 5.2.2.5 Under/Over Frequency Protection HEBB -- 5.3 Test Setup and RealTime Results -- 5.3.1 Case I -- 5.3.2 Case II -- 5.4 Summary -- Chapter 6 Adaptive TimeStepping Based RealTime EMT Emulation -- 6.1 Overview -- 6.2 Nonlinear Solution and Adaptive TimeStepping Schemes -- 6.2.1 Nonlinear Element Solution Methods -- 6.2.1.1 Newton-Raphson Method -- 6.2.1.2 Piecewise Linearization (PWL) Method -- 6.2.1.3 Piecewise NR Method -- 6.2.2 Adaptive TimeStepping Schemes -- 6.2.2.1 Local Truncation Error Method -- 6.2.2.2 Iteration Count Method -- 6.2.2.3 DVDT or DIDT Method -- 6.2.3 Combinations of Adaptive TimeStepping Schemes -- 6.2.3.1 Measurements and Restrictions for RealTime Emulation -- 6.2.4 Case Studies -- 6.2.4.1 Diode FullBridge Circuit -- 6.2.4.2 Power Transmission System -- 6.2.4.3 FPGA Implementation -- 6.2.4.4 RealTime Emulation Results -- 6.3 Adaptive TimeStepping Universal Line Model and Universal Machine Model for RealTime Hardware Emulation -- 6.3.1 Subsystem Based Adaptive TimeStepping Scheme -- 6.3.2 Adaptive TimeStepping ULM and UM Models -- 6.3.2.1 ULM Computation -- 6.3.2.2 Universal Machine Model Computation -- 6.3.3 RealTime Emulation Case Study -- 6.3.3.1 Hardware Implementation -- 6.3.3.2 Latency and Hardware Resource Utilization -- 6.3.4 Results and Validation -- 6.3.4.1 Validation of the ULM Model -- 6.3.4.2 RealTime Emulation Results -- 6.4 Summary -- Chapter 7 Power Electronic Switches -- 7.1 Overview -- 7.2 IGBT/Diode Nonlinear Behavioral Model -- 7.2.1 Power Diode -- 7.2.1.1 Mathematical Model -- 7.2.1.2 Hardware Module Architecture -- 7.2.2 IGBT. 7.2.2.1 Model Formulation -- 7.2.2.2 Hardware Module Architecture -- 7.2.2.3 Multiple Parallel Devices -- 7.2.3 ElectroThermal Network -- 7.2.4 Hardware Emulation Results -- 7.3 PhysicsBased Nonlinear IGBT/Diode Model -- 7.3.1 PhysicsBased Nonlinear p-i-n Diode Model -- 7.3.1.1 Model Formulation -- 7.3.1.2 Model Discretization and Linearization -- 7.3.1.3 Hardware Emulation on FPGA -- 7.3.2 Physics Based Nonlinear IGBT Model -- 7.3.2.1 Model Formulation -- 7.3.2.2 Model Discretization and Linearization -- 7.3.2.3 Hardware Emulation on FPGA -- 7.3.3 Hardware Emulation Results -- 7.3.3.1 Test circuit -- 7.3.3.2 Results and comparison -- 7.4 IGBT/Diode CurveFitting Model -- 7.4.1 Linear Static CurveFitting Model -- 7.4.1.1 Static Characteristics -- 7.4.1.2 Switching Transients -- 7.4.2 Nonlinear Dynamic CurveFitting Model -- 7.4.3 Hardware Emulation Results -- 7.5 Summary -- Chapter 8 AC-DC Converters -- 8.1 Overview -- 8.2 Detailed Model -- 8.2.1 Detailed Equivalent Circuit Model -- 8.3 Equivalenced DeviceLevel Model -- 8.3.1 Power Loss Calculation -- 8.3.2 Thermal Network Calculation -- 8.3.3 Hardware Emulation of SM Model on FPGA -- 8.3.4 MMC System Hardware Emulation -- 8.3.5 RealTime Emulation Results -- 8.3.5.1 Test Circuit and Hardware Resource Utilization -- 8.3.5.2 Results and Comparison for Single Phase FiveLevel MMC -- 8.3.5.3 Results for ThreePhase NineLevel

MMC -- 8.4 VirtualLinePartitioned DeviceLevel Models -- 8.4.1 TLM
Link Partitioning -- 8.4.2 Hardware Design on FPGA -- 8.4.2.1
Hardware Platform -- 8.4.2.2 Controller Emulation -- 8.4.2.3 MMC
Emulation on FPGA -- 8.4.3 RealTime Emulation Results -- 8.4.3.1
MMC -- 8.4.3.2 Induction Machine Driven by FiveLevel MMC -- 8.5
MMC Partitioned by Coupled Voltage-Current Sources -- 8.5.1 V-I
Coupling -- 8.5.2 Hardware Emulation Case of NBMBased MMC.
8.5.2.1 Power Converter HIL Emulation.
