

1. Record Nr.	UNINA9910555250603321
Autore	Lian Ryan Kuo-Lung
Titolo	Harmonic modeling of voltage source converters using simple numerical methods // Ryan Kuo-Lung Lia, Ramadhani Kurniawan Subroto, Bing Hao Lin
Pubbl/distr/stampa	Hoboken, New Jersey : , : John Wiley & Sons, Incorporated, , [2021] ©2021
ISBN	1-119-52715-5 1-119-52719-8 1-119-52714-7
Descrizione fisica	1 online resource (419 pages)
Collana	IEEE Press.
Disciplina	621.3815322
Soggetti	Harmonics (Electric waves) - Mathematical models Electromagnetic interference - Mathematical models Electric power-plants - Equipment and supplies Electric current converters - Mathematical models Numerical analysis Electronic books.
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Nota di bibliografia	Includes bibliographical references and index.
Nota di contenuto	Cover -- Title Page -- Copyright -- Contents -- Preface -- Acknowledgments -- Symbols -- Chapter 1 Fundamental Theory -- 1.1 Background -- 1.2 Definition of Harmonics -- 1.3 Fourier Series -- 1.3.1 Trigonometric Form -- 1.3.2 Phasor Form -- 1.3.3 Exponential Form -- 1.4 Waveform Symmetry -- 1.4.1 Even Symmetry -- 1.4.2 Odd Symmetry -- 1.4.3 HalfWave Symmetry -- 1.5 Phase Sequence of Harmonics -- 1.6 Frequency Domain and Harmonic Domain -- 1.7 Power Definitions -- 1.7.1 Average Power -- 1.7.2 Apparent and Reactive Power -- 1.8 Harmonic Indices -- 1.8.1 Total Harmonic Distortion (THD) -- 1.8.2 Total Demand Distortion (TDD) -- 1.8.3 True Power Factor -- 1.9 Detrimental Effects of Harmonics -- 1.9.1 Resonance -- 1.9.2 Misoperations of Meters and Relays -- 1.9.3 Harmonics Impact on Motors -- 1.9.4 Harmonics Impact on Transformers -- 1.10 Characteristic Harmonic and NonCharacteristic

Harmonic -- 1.11 Harmonic Current Injection Method -- 1.12 Steady State vs. Transient Response -- 1.13 SteadyState Modeling -- 1.14 LargeSignal Modeling vs. SmallSignal Modeling -- 1.15 Discussion of IEEE Standard (STD) 519 -- 1.16 Supraharmonics -- Chapter 2 Power Electronics Basics -- 2.1 Some Basics -- 2.2 Semiconductors vs. Wide Bandgap Semiconductors -- 2.3 Types of Static Switches -- 2.3.1 Uncontrolled Static Switch -- 2.3.2 SemiControllable Switches -- 2.3.3 Controlled Switch -- 2.4 Combination of Switches -- 2.5 Classification Based on Commutation Process -- 2.6 Voltage Source Converter vs. Current Source Converter -- Chapter 3 Basic Numerical Iterative Methods -- 3.1 Definition of Error -- 3.2 The Gauss-Seidel Method -- 3.3 PredictorCorrector -- 3.4 Newton's Method -- 3.4.1 Root Finding -- 3.4.2 Numerical Integration -- 3.4.3 Power Flow -- 3.4.4 Harmonic Power Flow -- 3.4.5 Shooting Method -- 3.4.6 Advantages of Newton's Method -- 3.4.7 QuasiNewton Method.

3.4.8 Limitation of Newton's Method -- 3.5 PSO -- Chapter 4 Matrix Exponential -- 4.1 Definition of Matrix Exponential -- 4.2 Evaluation of Matrix Exponential -- 4.2.1 Inverse Laplace Transform -- 4.2.2 Cayley-Hamilton Method -- 4.2.3 Padé Approximation -- 4.2.4 Scaling and Squaring -- 4.3 Krylov Subspace Method -- 4.4 Krylov Space Method with Restarting -- 4.5 Application of Augmented Matrix on DCDC Converters -- 4.6 Runge-Kutta Methods -- Chapter 5 Modeling of Voltage Source Converters -- 5.1 SinglePhase TwoLevel VSCs -- 5.1.1 Switching Functions -- 5.1.2 Switched Circuits -- 5.2 ThreePhase Two Level VSCs -- 5.3 ThreePhase Multilevel Voltage Source Converter -- 5.3.1 Multilevel PWM -- 5.3.2 Diode Clamped Multilevel VSCs -- 5.3.3 Flying Capacitor Multilevel VSCs -- 5.3.4 Cascaded MultiLevel VSCs -- 5.3.5 Modular MultiLevel VSC -- Chapter 6 Frequency Coupling Matrices -- 6.1 Construction of FCM in the Harmonic Domain -- 6.2 Construction of FCM in the Time Domain -- Chapter 7 General Control Approaches of a VSC -- 7.1 Reference Frame -- 7.1.1 Stationaryabc Frame -- 7.1.2 Stationary\dot{x} -- 7.1.3 Synchronous$\dot{\theta}$ -- 7.1.4 PhaseLocked Loop -- 7.2 Control Strategies -- 7.2.1 VectorCurrent Controller -- 7.2.2 Direct Power Controller -- 7.2.3 DC bus Voltage Controller -- 7.2.4 Circulating Current Controller -- Chapter 8 Generalized SteadyState Solution Procedure for ClosedLoop Converter Systems -- 8.1 Introduction -- 8.2 Generalized Procedure -- 8.2.1 Step 1: Determine How and Where to Break the Loop -- 8.2.2 Step 2: Check if the Calculation Flows of the Broken System are Feasible.

8.2.3 Step 3: Determine What Domain of Each Component in the System Should be Modeled -- 8.2.4 Step 4: Formulate the Mismatch Equations -- 8.2.5 Step 5: Iterate to Find the Solution -- 8.3 Previously Proposed Methods Derived from the Proposed Solution Procedures -- 8.3.1 SteadyState Methods Derived from LoopBreaking 1 Method -- 8.3.2 SteadyState Methods Derived from LoopBreaking 2 Method -- 8.4 The LoopBreaking 3 Method -- Chapter 9 LoopBreaking 1 Method -- 9.1 A Typical TwoLevel VSC with AC Current Control and DC Voltage Control -- 9.2 LoopBreaking 1 Method for a TwoLevel VSC -- 9.2.1 Block 1 -- 9.2.2 Current Controller Block -- 9.2.3 Voltage Controller Block -- 9.3 Solution Flow Diagram -- 9.3.1 Initialization -- 9.3.2 Jacobian Matrix -- 9.3.3 Number of Modulating Voltage Harmonics to be Included -- Chapter 10 LoopBreaking 2 Method for Solving a VSC -- 10.1 Modeling for a ClosedLoop DCDC Converter -- 10.1.1 Model of the Buck Converter -- 10.1.2 Constraints of SteadyState -- 10.1.3

Switching Time Constraints -- 10.1.4 Solution Flow Diagram -- 10.2
TwoLevel VSC Modeling: OpenLoop Equations -- 10.2.1 SteadyState
Constraints -- 10.2.2 Switching Time Constraints -- 10.2.3 Solution
Flow Diagram -- 10.2.4 Initialization -- 10.2.5 Jacobian Matrix -- 10.3
Comparison Between the LB 1 and LB 2 Methods -- 10.3.1 Case #1:
Balanced System -- 10.3.2 Case #2: Unbalanced System with AC
Waveform Exhibiting HalfWave Symmetry -- 10.3.3 Case #3:
Unbalanced System, No Waveform Symmetry -- 10.4 LargeSignal
Modeling for LineCommutated Power Converter -- 10.4.1
Discontinuous Conduction Mode -- 10.4.2 Continuous Conduction
Mode -- 10.4.3 SteadyState Constraint Equations -- 10.4.4 General
Comments -- Chapter 11 LoopBreaking 3 Method -- 11.1 OpenDSS --
11.2 Interfacing OpenDSS with MATLAB -- 11.3 Interfacing OpenDSS
with Harmonic Models of VSCs.
Chapter 12 SmallSignal Harmonic Model of a VSC -- 12.1 Problem
Statement -- 12.2 Gauss-Seidel LB 3 and Newton LB 3 -- 12.2.1
Current Injection Method -- 12.2.2 Norton Circuit Method -- 12.3
SmallSignal Analysis of DCDC Converter -- 12.4 SmallSignal Analysis
of a TwoLevel VSC -- 12.4.1 Approach from Section 12.3 -- 12.4.2
Simpler Approach -- Chapter 13 Parameter Estimation for a Single VSC
-- 13.1 Background on Parameter Estimation -- 13.2 Parameter
Estimator Based on WhiteBoxandBlackBox Models -- 13.3 Estimation
Validations -- 13.3.1 Experimental Validation -- 13.3.2 PSCAD/EMTDC
Validation -- Chapter 14 Parameter Estimation for Multiple VSCs with
Domain Adaptation -- 14.1 Introduction of Deep Learning -- 14.2
Domain Adaptation -- 14.3 Parameter Estimation for Multiple VSCs --
14.4 Notations for DA -- 14.5 Supervised Domain Adaptation for
Regression -- 14.6 Supervised Domain Adaptation for Classification --
14.7 Test Setup -- 14.7.1 Data Generator -- 14.7.2 Data Preprocessing
-- 14.8 Performance Metrics -- 14.8.1 R square (Regression) -- 14.8.2
Mean Absolute Percentage Error, MAPE (Regression) -- 14.8.3 Accuracy
(Classification) -- 14.8.4 F1 score (Classification) -- 14.9 Test Results
-- 14.9.1 Classification Task on Multiple VSC -- 14.9.2 Regression
Task on Multiple VSC -- 14.10 Software for Running the Codes --
14.11 Implementation of Domain Adaptation -- 14.11.1 Data
Generation -- 14.11.2 Regression -- 14.11.3 Classification Network --
References -- Index -- EULA.
