

|                         |   |
|-------------------------|---|
| 1. Record Nr.           | UNINA9910642871203321   |
| Autore                  | Randa James   |
| Titolo                  | Precision Measurement of Microwave Thermal Noise  |
| Pubbl/distr/stampa      | Newark : , : John Wiley & Sons, Incorporated, , 2022<br>©2023   |
| ISBN                    | 1-119-91011-0<br>1-119-91010-2<br>1-119-91012-9   |
| Descrizione fisica      | 1 online resource (179 pages)   |
| Lingua di pubblicazione | Inglese   |
| Formato                 | Materiale a stampa  |
| Livello bibliografico   | Monografia  |
| Nota di contenuto       | Cover -- Title Page -- Copyright -- Contents -- Preface -- Chapter 1 Background -- 1.1 Nyquist's Theorem and Noise Temperature -- 1.1.1 Nyquist's Theorem -- 1.1.2 Limits and Numbers -- 1.1.3 Definition of Noise Temperature -- 1.1.4 Excess Noise Ratio and T0 -- 1.2 Microwave Networks -- 1.2.1 Notation -- 1.2.2 Noise Correlation Matrix and Bosma's Theorem -- 1.2.3 Power Ratios -- 1.2.4 Noise Temperature Translation Through a Passive Device -- References -- References -- Chapter 2 NoiseTemperature Standards -- 2.1 Introduction -- 2.2 Ambient Standards -- 2.3 Hot (Oven) Standards -- 2.4 Cryogenic Standards -- 2.4.1 Coaxial Standards -- 2.4.2 Waveguide Standards -- 2.5 Other Standards and Noise Sources -- 2.5.1 Tunable Primary Standards -- 2.5.2 "Equivalent Hot Standard" Based on RF Power -- 2.5.3 Secondary Standards -- 2.5.4 Synthetic Primary Standards -- References -- Chapter 3 NoiseTemperature Measurement -- 3.1 Background -- 3.2 TotalPower Radiometer -- 3.2.1 Idealized Case -- 3.2.2 Nonideal Case -- 3.2.3 Radiometer Equation for Isolated TotalPower Radiometer -- 3.2.4 TotalPower Radiometer Design -- 3.2.5 Radiometer Testing -- 3.3 TotalPower Radiometer Uncertainties -- 3.3.1 TypeA Uncertainties -- 3.3.2 TypeB Uncertainties -- 3.3.3 Sample Results -- 3.4 Other Radiometer Designs -- 3.4.1 Switching or Dicke Radiometer -- 3.4.2 Digital Radiometer -- |

3.5 Measurements through Adapters -- 3.6 Traceability and Inter laboratory Comparisons -- References -- Chapter 4 Amplifier Noise -- 4.1 Noise Figure, Effective Input Noise Temperature -- 4.2 Noise Temperature Definition Revisited -- 4.3 Noise Figure Measurement, Simple Case -- 4.4 Definition of Noise Parameters -- 4.4.1 Circuit Treatment of Noisy Amplifier -- 4.4.2 Wave Representation of Noise Parameters -- 4.5 Measurement of Noise Parameters -- 4.5.1 General Measurement Setup. 4.5.2 Fit to NoiseFigure Parameterization -- 4.5.3 Fit to Noise Temperature or Power Parameterization -- 4.5.4 Possible Variations When Using the Wave Formulation -- 4.5.5 Choice of Input Terminations -- 4.5.6 Commercial Systems, SourcePull Measurements -- 4.5.7 Frequency-Variation Method -- 4.6 Uncertainty Analysis for NoiseParameter Measurements -- 4.6.1 Simple Considerations -- 4.6.2 Full Analysis -- 4.6.3 Input Uncertainties -- 4.6.4 General Features and Sample Results -- 4.7 Simulations and Strategies -- References -- Chapter 5 OnWafer Noise Measurements -- 5.1 Introduction -- 5.2 OnWafer Microwave Formalism -- 5.2.1 Traveling Waves vs. Pseudo Waves -- 5.2.2 OnWafer Reference Planes -- 5.3 NoiseTemperature Measurements -- 5.4 OnWafer NoiseParameter Measurements -- 5.4.1 General -- 5.4.2 RadiometerBased Systems -- 5.4.3 Commercial Systems and ReferencePlane Considerations -- 5.4.4 "Enhanced" or ModelAssisted Measurements -- 5.5 Uncertainties -- 5.5.1 Differences from Packaged Amplifiers -- 5.5.2 General Features and Properties -- 5.5.3 Measurement Strategies -- References -- Chapter 6 NoiseParameter Checks and Verification -- 6.1 Measurement of Passive or Previously Measured Devices -- 6.2 Physical Bounds and Model Predictions -- 6.3 Tandem or Hybrid Measurements -- References -- Chapter 7 Cryogenic Amplifiers -- 7.1 Background -- 7.1.1 Introduction -- 7.1.2 VacuumFluctuation Contribution -- 7.2 Measurement of the Matched Noise Figure -- 7.2.1 ColdAttenuator Method -- 7.2.2 Internal Hot-Cold Method -- 7.2.3 Full Characterization Measurements -- 7.3 NoiseParameter Measurement -- References -- Chapter 8 Multiport Amplifiers -- 8.1 Introduction -- 8.2 Formalism and Noise Matrix -- 8.3 Definition of Noise Figure for Multiports -- 8.4 Degradation of SignaltoNoise Ratio. 8.5 ThreePort Example - Differential Amplifier with Reflectionless Terminations -- 8.5.1 Motivation -- 8.5.2 Characteristic Noise Temperature, Gains, and Effective Input Noise Temperature -- 8.5.3 Noise Figure -- 8.5.4 Practical Applications -- 8.6 FourPort Example with Reflectionless Terminations -- References -- Chapter 9 Remote Sensing Connection -- 9.1 Introduction -- 9.2 Theory for Standard Radiometer -- 9.3 StandardRadiometer Measurements -- 9.3.1 Determination of -- 9.3.2 Determination of Illumination Efficiency, IE -- 9.3.2.1 Measurements of a Standard Target -- 9.4 Standard Target Design -- 9.5 Target Reflectivity Effects -- 9.5.1 Effect of Target Reflectivity -- 9.5.2 Measurement of Target Reflectivity -- References -- Index -- EULA.

---