

1. Record Nr.	UNINA9910780035303321
Autore	Parssinen Aarno
Titolo	Direct conversion receivers in wide-band systems [[electronic resource] /] / by Aarno Parssinen
Pubbl/distr/stampa	Boston, : Kluwer Academic Publishers, c2001
ISBN	1-280-20032-4 9786610200320 0-306-47545-6
Edizione	[1st ed. 2001.]
Descrizione fisica	1 online resource (251 p.)
Collana	The Kluwer international series in engineering and computer science ; ; SECS 655
Disciplina	621.384/18
Soggetti	Integrated circuits - Design and construction Broadband communication systems - Equipment and supplies Radio circuits - Design and construction Radio - Transmitter-receivers - Equipment and supplies - Design and construction
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Note generali	Description based upon print version of record.
Nota di bibliografia	Includes bibliographical references.
Nota di contenuto	System Requirements for Radio Receivers in Wireless Communications -- Receiver Architectures -- Direct Conversion Receivers -- Circuit Implementations.
Sommario/riassunto	This book is based on my doctoral thesis at the Helsinki University of Technology. Several different projects during five years guided me from the basics of the RF IC design to the implementations of highly integrated radio receiver chips. Sharing time and effort between IC and system issues is not always straightforward. I have been lucky to follow both topics and share experiences with diligent and enthusiastic people having different specialities. As a result, this book will cover a wide range of different topics needed in the design of highly integrated radio receivers. Experiences from the first receiver prototypes for the third generation cellular systems form the basis of this book. Most of the issues are directly related to the early proposals of European and Japanese standardization organizations. For example, the chip rate was originally set to 4. 096 Mcps in a wide-band CDMA channel. I have kept

that number in the book in most of the examples although it has been later changed to 3.84 Mcps. I hope that the readers will accept that and the possible other incompatibilities to the latest specifications. At least in the research phase the changes even in the most essential requirements are definitely not a rare incident and IC designers should be able to react and modify their designs as soon as they can.
