

1. Record Nr.	UNISA996280427203316
Titolo	IEEE Standard for Information Technology . Specific Requirements Part 3, Carrier Sense Multiple Access with Collision Detection (CSMA/CD) Access Method and Physical Layer : Telecommunications and Information Exchange Between Systems - Local and Metropolitan Area Networks // IEEE
Pubbl/distr/stampa	New York, N.Y. : , : IEEE, , 2005
ISBN	0-7381-4741-9
Edizione	[(Revision of IEEE Std 802.3-2002 including all).]
Descrizione fisica	1 online resource (2695 pages)
Collana	IEEE Std ; ; 802.3-2005
Disciplina	004.6
Soggetti	Local area networks (Computer networks)
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Sommario/riassunto	<p>Ethernet local area network operation is specified for selected speeds of operation from 1 Mb/s to 10 Gb/s using a common media access control (MAC) specification, management information base (MIB), and capability for Link Aggregation of multiple physical links into a single logical link. The Carrier Sense Multiple Access with Collision Detection (CSMA/CD) MAC protocol specifies shared medium (half duplex) operation, as well as full duplex operation. Speed specific Media Independent Interfaces (MIIs) allow use of selected physical layer (PHY) interfaces for operation over coaxial, twisted pair or fiber optic cables. System considerations for multisegment shared access networks describe the use of Repeaters which are defined for operational speeds up to 1000 Mb/s. Local Area Network (LAN) operation is supported at all speeds. Other specified capabilities include: various PHY types for access networks, PHYs suitable for metropolitan area network applications, and the provision of power over selected twisted pair PHY types. (Supersedes 802.3-2002 + 802.3ae-2002 + 802.3af-2003 + 802.3ah-2004 + 802.3aj-2003 + 802.3ak-2004). An interpretation is available at http://standards.ieee.org/findstds/interps/802.3-2005_interp.html.</p>

