

1. Record Nr.	UNISA996280647003316
Titolo	IEEE standard for pad-mounted-type, self-cooled, single-phase distribution transformers 250 kVA and smaller : high voltage, 34 500 GrdY/19 920 V and below ; low voltage, 480/240 V and below
Pubbl/distr/stampa	New York : , : IEEE, , 2014
ISBN	0-7381-9281-3
Descrizione fisica	1 online resource (22 pages)
Collana	IEEE Std
Disciplina	621.314
Soggetti	Electric transformers
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Nota di bibliografia	Includes bibliographical references.
Sommario/riassunto	Certain electrical, dimensional, and mechanical characteristics are covered in this standard, and certain safety features of single-phase, 60-Hz, mineral-oil-immersed, self-cooled, pad-mounted, compartmental-type distribution transformers are taken into consideration. These transformers are rated 250 kVA and smaller with high voltages of 34 500 GrdY/19 920 V and below and with low voltages of 480/240 V and be low. These transformers are generally used for step-down purposes from an underground primary cable supply. The connector, bushing, and terminal arrangements for radial or loop feed systems are covered in this standard. The electrical and mechanical requirements of any accessory devices that may be supplied with the transformer are not covered in this standard.