

1. Record Nr.	UNISA996281047403316
Titolo	IEEE Std C37.13-2015 (Revision of IEEE Std C37.13-2008) : IEEE standard for low-voltage AC power circuit breakers used in enclosures // Institute of Electrical and Electronics Engineers
Pubbl/distr/stampa	Piscataway, New Jersey : , : IEEE, , 2015
ISBN	1-5044-0592-7
Descrizione fisica	1 online resource (46 pages)
Disciplina	621.317
Soggetti	Electric circuit-breakers Electric circuits - Alternating current
Lingua di pubblicazione	Inglese
Formato	Materiale a stampa
Livello bibliografico	Monografia
Sommario/riassunto	The following enclosed low-voltage ac power circuit breakers are covered in this standard: a. stationary or drawout type of two-, three-, or four-pole construction, with one or more rated maximum voltages of 1058 V, 730 V, 635 V (600 V for units incorporating fuses), 508 V, or 254 V for application on systems having nominal voltages of 1000 V, 690 V, 600 V, 480 V, or 240 V; b. unfused or fused circuit breakers; c. manually or power operated; and d. with or without electromechanical or electronic trip devices. Service conditions, ratings, functional components, temperature limitations and classifications of insulating materials, insulation (dielectric) withstand voltage requirements, test procedures, application, and the preferred ratings are discussed in this standard.